



TECHNICAL DATA OF THE COURT

Interior dimensions of the field:

	STANDARD	MINIMUM
LENGTH	9.80 m	9.50 m
WIDTH	4.80 m	4.50 m
NET	2.70 m	2.50 m
DEPTH OF CAGES	0.30 m	0.30 m

Maximum dimensions of obstruction
outside of the field of sides:

STANDARD MEASURES

LENGTH: 10.52 m	WIDTH: 5.13 m	HEIGHT: 3.12 m
-----------------	---------------	----------------

**Minimum dimensions of obstruction
outside of the field of sides:**

MINIMUM MEASURES

LENGTH: 10.22 m	WIDTH: 4.83 m	HEIGHT: 2.92 m
------------------------	----------------------	-----------------------

Opaque walls

Composed of a panel made of polyurethane foam "sandwiched" between two steal panels of 6/10, colored white. Total thickness of opaque plates: 60mm. Dimension of opaque plates: 2.70 m by 1.0 m approximately. These plates are slotted together in order to obtain the desired dimensions of the field. An aluminum folding lacquered white will be fitted into the top and bottom of the panels to ensure the rigidity of the whole.

Transparent walls

Composed of wind bracing mm 15 plexiglass of 3 m in height plexiglass panels 15mm transparent fixed by aluminum dishes 50 x 3 lacquered white and stainless steel screws of 12 x 25. The plexiglass frames are 1.39 m wide and 2.55 m in height, with a rabbet of 15 x 3 on the two interior heights in order to insert the flat mounting while keeping a flat surface of the inside of the court.

Goals

On the two smaller walls of the Jorkyball court, 2 goals of 1.1 m high x 1.1 m length and 0.30 m depth are cut. Each goal is reinforced by an iron frame lacquered in red.. Each goal is completed with a specially designed net.

Fixing to the floor

The plexiglass installments are fixed to the ground by plated screwed into the existing slab. Each plate includes 3 screws. The aluminum profiles are coupled and screwed onto the boards. The slab must be perfectly flat and of a thickness of 12 cm minimum.

The ceiling

A backbone in square aluminum tubes is raised by plates in order to distance by 300mm the net from the structure which ensures the rigidity of the field.

A net covers the surface of the ceiling with a final height to the ground of m 2.70.

The entry door

The entry door measures mm 2005 x mm 720 and is always cut on a transparent wall to which a framework with lock and its hinges are added in plexiglass.

The floor

The floor is covered with a synthetic turf with the game areas incorporated. The carpet must be sanded with 1,000 kg of sand per court.